

January 29, 2004  
Case No. US 000309 (7790/210)  
Serial No.: 09/735,151  
Filed: December 12, 2000  
Page 2 of 12

**CLAIM AMENDMENTS**

A listing of the entire set of claims 1-44 (including amendments to claims 34-41) is submitted herewith per 37 CFR §1.121. This listing of claims 1-44 will replace all prior versions, and listings, of claims in the application.

1.-24. (Cancelled)

25. (Previously Presented) A LED backlight for an LCD display, comprising:  
a primary circuit for generating a primary voltage;  
a first secondary circuit coupled to said primary circuit for receiving a first secondary voltage as a function of the primary voltage, said first secondary circuit including

a first sub-array of LEDs of a first color,

a first sub-array switch operable in a first ON state for allowing a flow of a first LED current through said first sub-array of LEDs, the first LED current being a function of said first secondary voltage, and

a first sub-array controller for controlling an operation of said first switch in the first ON state; and

a second secondary circuit coupled to said primary circuit for receiving a second secondary voltage as a function of the primary voltage, said second secondary circuit including

a second sub-array of LEDs of a second color,

a second sub-array switch operable in a second ON state for allowing a flow of a second LED current through said second sub-array of LEDs, the second LED current being a function of said second secondary voltage, and

a second sub-array controller for controlling an operation of said second switch in the second ON state,

wherein said first sub-array controller controls the operation of said first sub-array switch in the first ON state and said second sub-array controller controls the operation of said second sub-array switch in the second ON state in a mutually exclusive manner.

January 29, 2004  
Case No. US 000309 (7790/210)  
Serial No.: 09/735,151  
Filed: December 12, 2000  
Page 3 of 12

- C1
26. (Previously Presented) The LED backlight of claim 25,  
wherein said first sub-array controller controls the operation of said first  
switch in the first ON state as a function of a first feedback voltage indicative of a  
first LED voltage across said first sub-array of LEDs.
27. (Previously Presented) The LED backlight of claim 26,  
wherein said second sub-array controller controls the operation of said second  
switch in the second ON state as a function of a second feedback voltage indicative of  
a second LED voltage across said second sub-array of LEDs.
28. (Previously Presented) The LED backlight of claim 25,  
wherein said first sub-array controller controls the operation of said first  
switch in the first ON state as a function of a first reference current indicative of a  
first commanded light output of said first sub-array of LEDs.
29. (Previously Presented) The LED backlight of claim 28,  
wherein said second sub-array controller controls the operation of said second  
switch in the second ON state as a function of a second reference current indicative of  
a second commanded light output of said second sub-array of LEDs.
30. (Previously Presented) The LED backlight of claim 25,  
wherein said first sub-array controller modulates the first LED current when  
said first sub-array switch is operating in the first ON state.
31. (Previously Presented) The LED backlight of claim 30,  
wherein said second sub-array controller modulates the second LED current  
when said second sub-array switch is operating in the second ON state.
32. (Previously Presented) The LED backlight of claim 25,

January 29, 2004  
Case No. US 000309 (7790/210)  
Serial No.: 09/735,151  
Filed: December 12, 2000  
Page 4 of 12

wherein said first sub-array controller controls at least one of a first pulse-amplitude modulation, a first pulse-width modulation, and a first pulse-frequency modulation of the first LED current when said first sub-array switch is operating in the first ON state.

33. (Previously Presented) The LED backlight of claim 32,

wherein said second sub-array controller controls at least one of a second pulse-amplitude modulation, a second pulse-width modulation, and a second pulse-frequency modulation of the second LED current when said second sub-array switch is operating in the second ON state.

34. (Currently Amended) The LED backlight of claim 25,

wherein said first secondary voltage is applied between a first ~~node~~ point and a second ~~node~~ point;

wherein said first sub-array switch includes a first current path ~~connected to~~ for connecting said first ~~node~~ point and a ~~third node~~ to said first sub-array of LEDs when said first sub-array switch is operating in the first ON state;

~~wherein said first sub-array of LEDs is connected to said third node;~~

wherein said first sub-array switch further includes a first control input for controlling the operation of said first sub-array switch in the first ON state; and

wherein said first sub-array controller is connected to said first control input to thereby control the operation of said first sub-array switch in the first ON state.

35. (Currently Amended) The LED backlight of claim 34,

wherein said second secondary voltage is applied between a ~~fourth node~~ third point and a ~~fifth node~~ fourth point;

wherein said second sub-array switch includes a second current path ~~connected to~~ connecting said ~~fourth node~~ third point and a ~~sixth node~~ to said second sub-array of LEDs when said second sub-array switch is operating in the second ON state;

~~wherein said second sub-array of LEDs is connected to said sixth node;~~

January 29, 2004  
Case No. US 000309 (7790/210)  
Serial No.: 09/735,151  
Filed: December 12, 2000  
Page 5 of 12

wherein said second sub-array switch further includes a second control input for controlling the operation of said second sub-array switch in the second ON state; and

wherein said second sub-array controller is connected to said second control input to thereby control the operation of said second sub-array switch in the second ON state.

36. (Currently Amended) The LED backlight of claim 26,  
wherein said first secondary voltage is applied between a first ~~node point~~ and a second ~~node point~~;

wherein said first sub-array switch includes a first current path ~~connected to~~ for connecting said first node point and a third node to said first sub-array of LEDs when said first sub-array switch is operating in the first ON state;

~~wherein said first sub-array of LEDs is connected to said third node and a fourth node;~~

wherein said first sub-array switch further includes a first control input for controlling the operation of said first sub-array switch in the first ON state; and

wherein said first sub-array controller is connected to said first control input to thereby control the operation of said first sub-array switch in the first ON state;

~~wherein said first sub-array controller is further connected to said fourth node to determine the first feedback voltage.~~

37. (Currently Amended) The LED backlight of claim 36,

wherein said first secondary circuit further includes a resistor connected to ~~said second node and said fourth node~~ said first sub-array of LEDs and said first sub-array controller to facilitate a determination of the first feedback voltage by said first sub-array controller.

38. (Currently Amended) The LED backlight of claim 27,

wherein said first secondary voltage is applied between a first ~~node point~~ and a second ~~node point~~;

January 29, 2004  
Case No. US 000309 (7790/210)  
Serial No.: 09/735,151  
Filed: December 12, 2000  
Page 6 of 12

wherein said first sub-array switch includes a first current path ~~connected to~~  
for connecting said first node point and a third node to said first sub-array of LEDs  
when said first sub-array switch is operating in the first ON state;

~~wherein said first sub-array of LEDs is connected to said third node and a~~  
~~fourth node;~~

wherein said first sub-array switch further includes a first control input for  
controlling the operation of said first sub-array switch in the first ON state;

wherein said first sub-array controller is connected to said first control input to  
thereby control the operation of said first sub-array switch in the first ON state; and

~~wherein said first sub-array controller is further connected to said third node~~  
~~and said fourth node to determine the first feedback voltage.~~

39. (Currently Amended) The LED backlight of claim 38,

wherein said first secondary circuit further includes a resistor connected to  
~~said second node and said fourth node~~ said first sub-array of LEDs and said first sub-  
array controller to facilitate a determination of the first feedback voltage by said first  
sub-array controller.

40. (Currently Amended) The LED backlight of claim 38,

wherein said second secondary voltage is applied between a ~~fifth node~~ third  
point and a ~~sixth node~~ fourth point;

wherein said second sub-array switch includes a second current path  
~~connected to for connecting said fifth node third point and a seventh node to said~~  
second sub-array of LEDs when said second sub-array switch is operating in the  
second ON state;

~~wherein said second sub-array of LEDs is connected to said seventh node and~~  
~~an eighth node;~~

wherein said second sub-array switch further includes a second control input  
for controlling the operation of said second sub-array switch in the second ON state;  
and

January 29, 2004

Case No. US 000309 (7790/210)

Serial No.: 09/735,151

Filed: December 12, 2000

Page 7 of 12

wherein said second sub-array controller is connected to said second control input to thereby control the operation of said second sub-array switch in the second ON state; and

~~wherein said second sub-array controller is further connected to said seventh node and said eighth node to determine the second feedback voltage.~~

41. (Currently Amended) The LED backlight of claim 40,

wherein said first secondary circuit further includes a first resistor connected to ~~said second node and said fourth node~~ to said first sub-array of LEDs and said first sub-array controller to facilitate a determination of the first feedback voltage by said first sub-array controller; and

wherein said second secondary circuit further includes a second resistor connected to ~~said sixth node and said eighth node~~ to said second sub-array of LEDs and said second sub-array controller to facilitate a determination of the second feedback voltage by said second sub-array controller.

42. (Previously Presented) The LED backlight of claim 25, further comprising:

a transformer including a first magnetic coupling of a primary winding and a first secondary winding,

wherein said primary circuit is connected to said primary winding to thereby apply the primary voltage across said primary winding whereby the first secondary voltage is applied across said first secondary winding, and

wherein said first secondary circuit is connected to said first secondary winding.

43. (Previously Presented) The LED backlight of claim 25,

wherein said transformer further includes

a first magnetic coupling of a primary winding and a first secondary winding, and

a second magnetic coupling of said primary winding and a second secondary winding;

January 29, 2004

Case No. US 000309 (7790/210)

Serial No.: 09/735,151

Filed: December 12, 2000

Page 8 of 12

wherein said primary circuit is connected to said primary winding to thereby apply the primary voltage across said primary winding whereby the first secondary voltage is applied across said first secondary winding and the second secondary voltage is applied across said second secondary winding; and

wherein said first secondary circuit is connected to said first secondary winding, and the second secondary circuit is connected to said second secondary winding.

44. (Previously Presented) The LED backlight of claim 25, further comprising:  
a third secondary circuit coupled to said primary circuit for receiving a third secondary voltage as a function of the primary voltage, said third secondary circuit including

a third sub-array of LEDs of a third color,

a third sub-array switch operable in a third ON state for allowing a flow of a third LED current through said third sub-array of LEDs, the third LED current being a function of said third secondary voltage, and

a third sub-array controller for controlling an operation of said third switch in the third ON state,

wherein said first sub-array controller controls the operation of said first sub-array switch in the first ON state, said second sub-array controller controls the operation of said second sub-array switch in the second ON state, and said third sub-array controller controls the operation of said third sub-array switch in the third ON state in a mutually exclusive manner.